

# Series **SS3000**

- Marine/Corrosive Environments • Washdown
- Fire Protection • Chemical/Food Transfer

**To handle 3/4" or 1" I.D. hose.**

- Economical manual rewind reels for long lengths of hose.
- Choose disc rewind or removable direct crank rewind.
- Supplied with spring-actuated pin lock.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1" female NPT threads.
- Standard outlet: 1" female NPT thread.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 1000 psi (69 bar).
- Standard fluid temperatures from -40° F to +250 °F (-40° C to +121° C). Optional temperature ratings available - consult factory.
- Consult factory for other pressures and temperatures.
- Consult factory for power reels for 1" hose.
- 304 stainless steel construction.



Standard configuration shown

**PARTS DRAWING – ISO 177**

Model Number	Hose Capacity of Reel feet m				Approx. Weight Crank Rewind lb. kg		Reel Dimensions*** in. mm			
	I.D. in. mm	Round Hose		Collapsible Hose	NET	SHIP	A	B	F	X
		3/4 19	1 25	1 25						
<b>SS3016-25-26-10.5</b>	<b>100</b>	<b>75</b>	<b>200</b>	<b>85</b>	<b>120</b>	<b>13</b>	<b>7.5</b>	<b>24.5</b>	<b>7.75</b>	
	30	23	61	39	54	330	191	622	197	
<b>SS3020-25-26-10.5</b>	<b>150</b>	<b>100</b>	<b>300</b>	<b>94</b>	<b>129</b>	<b>17</b>	<b>11.5</b>	<b>28.5</b>	<b>9</b>	
	46	30	91	43	59	432	292	723	229	
<b>SS3024-25-26-10.5</b>	<b>200</b>	<b>125</b>	<b>400</b>	<b>103</b>	<b>138</b>	<b>21</b>	<b>15.5</b>	<b>32.5</b>	<b>13</b>	
	61	38	122	47	63	533	394	825	330	
<b>SS3028-25-26-10.5</b>	<b>275</b>	<b>175</b>	<b>550</b>	<b>113</b>	<b>163</b>	<b>25.5</b>	<b>20</b>	<b>37</b>	<b>17.5</b>	
	84	53	168	51	74	648	508	939	445	

**Notes:**

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
3. Power rewind NOT available on these models.
4. Dimension "F" is the overall length of standard model reels. Crank rewind models, 3-1/2" clearance required to remove crank.
5. Subtract 5" from "F" dimension for disc rewind models.
6. Finish: Refer to page 2.
7. **Be sure to check dimensions and weights prior to ordering.**

**NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.

\*\*\*X, Y indicate mounting holes. See page 2.

