

COXREELS® PC Series spring driven "Power Cord" reels are heavy duty, industrial grade power sources. They replace tangled extension cords and self-retract to increase safety, productivity and efficiency. Modeled after the P and SH Series, the PC Series are designed for long-lasting, trouble-free performance even under the most demanding conditions.

PC SERIES


MODEL	ACCESSORY	CORD						APRX. LBS.	EZ-COIL MODELS	SIZE INDEX	
		AWG / NO COND.	CORD FT.	TYPE	VOLTS	AMPS					
FOR INDOOR USE ONLY! All models rated at 115 volts, 60 hz single phase only.											
PC13-3516-A†	Single Industrial Receptacle†	16 / 3	35	SJO	115	13	34	-		1	
PC13-5016-A†		16 / 3	50	SJO	115	13	36	EZ-PC13-5016-A		1	
PC19-7516-A		16 / 3	75	SJO	115	13	60	-		3	
PC24-0016-A		16 / 3	100	SJO	115	13	73	EZ-PC24-0016-A		4	
PC13-3512-A†		12 / 3	35	SJO	115	20	37	-		1	
PC13-5012-A†		12 / 3	50	SJO	115	20	40	EZ-PC13-5012-A		1	
PC19-7512-A		12 / 3	75	SJO	115	20	67	-		3	
PC24-0012-A		12 / 3	100	SJO	115	20	81	EZ-PC24-0012-A		4	
PC13-3512-B†		Quad "4 Plug" Industrial Receptacle†	12 / 3	35	SJO	115	20	38	-		1
PC13-5012-B†			12 / 3	50	SJO	115	20	41	EZ-PC13-5012-B		1
PC19-7512-B	12 / 3		75	SJO	115	20	68	-		3	
PC24-0012-B	12 / 3		100	SJO	115	20	84	EZ-PC24-0012-B		4	
PC13-3516-C†	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant†	16 / 3	35	SJTO	115	0.3	35	-		1	
PC13-5016-C†		16 / 3	50	SJTO	115	0.3	37	EZ-PC13-5016-C		1	
PC24-0016-C		16 / 3	100	SJTO	115	0.3	75	EZ-PC24-0016-C		4	
PC13-3516-D†	Fluorescent Angle Light with Tool Tap Plug†	16 / 3	35	SJTO	115	13	35	-		1	
PC13-5016-D†		16 / 3	50	SJTO	115	13	37	EZ-PC13-5016-D		1	
PC24-0016-D	16 / 3	100	SJTO	115	13	73	EZ-PC24-0016-D		4		
PC13-3516-E†	Incandescent Caged Drop Light with Tool Tap Plug†	16 / 3	35	SJTO	115	13	34	-		1	
PC13-5016-E†		16 / 3	50	SJTO	115	13	36	EZ-PC13-5016-E		1	
PC19-7516-E		16 / 3	75	SJTO	115	13	60	-		3	
PC24-0016-E		16 / 3	100	SJTO	115	13	73	EZ-PC24-0016-E		4	
PC13-3516-F†	Duplex G.F.C.I. Metal Industrial Receptacle†	16 / 3	35	SJO	115	13	36	-		1	
PC13-5016-F†		16 / 3	50	SJO	115	13	38	EZ-PC13-5016-F		1	
PC19-7516-F		16 / 3	75	SJO	115	13	60	-		3	
PC24-0016-F		16 / 3	100	SJO	115	13	73	EZ-PC24-0016-F		4	
PC13-3512-F†		12 / 3	35	SJO	115	20	39	-		1	
PC13-5012-F†		12 / 3	50	SJO	115	20	42	EZ-PC13-5012-F		1	
PC19-7512-F		12 / 3	75	SJO	115	20	67	-		3	
PC24-0012-F		12 / 3	100	SJO	115	20	83	EZ-PC24-0012-F		4	
PC19-7516-X	With Cord, Less Accessory	16 / 3	75**	SJO	115	13	60	-		3	
PC24-0016-X		16 / 3	100**	SJO	115	13	71	EZ-PC24-0016-X		4	
PC13-5012-X†	With Cord, Less Accessory	12 / 3	50**	SJO	115	20	40	EZ-PC13-5012-X		1	
PC19-7512-X		12 / 3	75**	SJO	115	20	66	-		3	
PC24-0012-X		12 / 3	100**	SJO	115	20	81	EZ-PC24-0012-X		4	
PC17-3510-X††		10 / 3	35**	SO	115	30	62	-		2	
PC17-5010-X††		10 / 3	50**	SO	115	30	67	-		2	
PC13L-5016††		Less Cord, Less Accessory	16 / 3	50*	SJO	115	25	31	EZ-PC13L-5016		1
PC19L-7516	16 / 3		75*	SJO	115	25	52	-		3	
PC24L-0016	16 / 3		100*	SJO	115	25	62	EZ-PC24L-0016		4	
PC13L-5012††	12 / 3		50*	SJO	115	25	29	EZ-PC13L-5012		1	
PC19L-7512	12 / 3		75*	SJO	115	25	53	-		3	
PC24L-0012	12 / 3		100*	SJO	115	25	64	EZ-PC24L-0012		4	
PC17L-5010††	10 / 3		-	-	115	35	49	-		2	

*Consult factory with 4 conductor requirements. **When not using specified cord type capacity may vary.

REEL DIMENSIONS

SIZE INDEX	W	H	L	X	Y	M	N
1	8½"	14⅞"	13½"	5"	6"	3"	5"
2	11"	18⅝"	17"	6"	6"	4"	5"
3	10⅞"	21"	19½"	6"	6"	4"	5"
4	10¼"	25½"	24"	6"	6"	4"	5"

Overall Dimensions Base Mounting Pattern



UL Listed †

UL Listed ††

PC SERIES: REEL SPECIFICATIONS

SLIP RING

- External heavy gauge CPC™ powder coated steel components cover for simple slip ring routine maintenance
- Electrical current runs through a 25AMP / 600V rated slip ring (35AMP on select models)
- Include 5' lead cable & grounding plug (except on less cord models)

DESIGN & STRUCTURE

- Single pedestal cord reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor & overhead positions
- Solid one piece, heavy gauge ¼" steel base & support post for maximum stability
- Coxreels' exclusive Super Hub™ dual axle support system on models with size index #3 & #4
- 1" solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- Controlled retraction speed up to 80% slower on EZ-COIL models :: See page 7 for details
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures cord at desired length

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Power Tools
- Light Source
- General Industrial
- Manufacturing Plants
- Automotive & Fleet Service Centers
- Construction Sites
- Workshops

ACCESSORIZE YOUR REEL :: PG 52

- Mounting Brackets
- Assorted Reel Accessories

