# P-W& SHW SERIES SPRING DRIVEN WELDING HOSE REELS

**COXREELS®** P-W and SHW Series spring driven "Welding" hose reels are the ideal solution for managing bulky twin line welding hose. The P-W Series, like the P Series, is more compact in size and shares the reputation for long lasting performance. The SHW Series has a larger chassis and frame to accommodate longer lengths of welding hose and Coxreels' original Super Hub dual axle support system for increased stability during operation, less vibration and

Hose supplied on reel is twin-siamese type meeting R.M.A. and C.G.A. type V.D. grade R specifications. Use of other types of hose is not recommended. Note: Do Not Exceed Listed Hose O.D. To Obtain Max. Length.



# P-W & SHW SERIES: REEL SPECIFICATIONS



- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel
- · Swivel lock bracket ensures maximum safety
- Swivel Seals: VITON®

### DESIGN & STRUCTURE

- · Designed for Oxy-Acetylene or "T" grade welding hose
- · Single pedestal reel with space saving design facilitates workplace organization
- · Guide arm adjusts to wall, floor & overhead positions
- · Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Coxreels' exclusive Super Hub™ dual axle support system on models with size index #2 & #3

### RETRACTION

- · Controlled retraction speed up to 80% slower on **EZ-COIL** models :: See page 7 for details
- · Enclosed factory tuned & matched cartridge-style spring motor
- · Non corrosive stainless steel spring, pawl & zinc plated ratchet
- · Multi-position non-sparking lock ratchet mechanism secures hose at desired length

### SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

### **POSSIBLE FIELDS OF APPLICATION**

- · Manufacturing Plants
- · Maintenance, Repair & Operations
- · Welding / Service Trucks
- Welding Shops
- · Garage Settings
- Automotive & Fleet Maintenance
- Pipelines

Hoses

· Mining, Construction & Railroad Operations

# ACCESSORIZE YOUR REEL :: PG 50

- · 0-Rings & Swivels
- · Mounting Brackets

Assorted Reel Accessories

HOSE

Oxygen-Acetylene welding hose reels

P-W-125	1/4"	25	200	46	EZ-P-W-125	P-WL-125†	39	1
P-W-135	1/4"	35	200	48	-	P-WL-135†	40	1
P-W-140	1/4"	40	200	51	-	P-WL-140†	42	1
SHW-N-150	1/4"	50	200	64	EZ-SHW-150	SHWL-N-150†	52	2
SHW-N-160	1/4"	60	200	76	-	SHWL-N-160†	61	3
SHW-N-175	1/4"	75	200	80	EZ-SHW-175	SHWL-N-175†	63	3
SHW-N-1100	1/4"	100	200	84	EZ-SHW-1100	SHWL-N-1100	62	3

To order EZ-Coil® equipped models less hose, please add prefix "EZ-". Less hose models comes with inlet hose

### DUAL FUEL WELDING HOSE REELS

I.D.

greater structural integrity.

Hose supplied on reel is twin-siamese type grade "T." Grade "T" reels and hoses are used for a wide variety of gases, such as MAPP, propane, natural and fuel. Note: Do Not Exceed Listed Hose O.D. To Obtain Max. Length.

property, factorial and fact. Notes by Not Except Listed 11000 Clark 110 Obtains Mark Long and									
HOSE						LESS HOSE		SIZE	
MODEL	I.D.	FT.	PSI	APRX. LBS.	AVAILABLE IN	MODEL	APRX. LBS.	INDEX	
P-WT-125	1/4"	25	200	46	EZ-P-WT-125	P-WTL-125†	39	1	
SHWT-N-150	1/4"	50	200	64	EZ-SHWT-150	SHWTL-N-150†	52	2	
SHWT-N-175	1/4"	75	200	80	EZ-SHWT-175	SHWTL-N-175†	63	3	
SHWT-N-1100	1/4"	100	200	84	EZ-SHWT-1100	SHWTL-N-1100	62	3	

To order EZ-Coil® equipped models less hose, please add prefix "EZ-". Less hose models comes with inlet hose

## **REEL DIMENSIONS** Technical Data Sheets Available On Website

SIZE INDEX	w	н	L	Х	Υ	М	N	
1	81/2"	18 <sup>5</sup> ⁄8"	17"	6"	6"	4"	5"	
2	101/4"	211/4"	191/2"	6"	6"	4"	5"	
3	101/4"	251/2"	24"	6"	6"	4"	5"	
	Overall Dimensions				se -	Mounting Pattern		







